

Sealed Lead-Acid Batteries

	Model: 12SB33P Voltage: 12V Capacity: 33Ah (C20) Int. resistance: 9 mOhm	Max charge I: 6.5 Amps Max discharge I: 330 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 194mm. Width: 130mm. Height: 167mm (167mm). Weight: 12kg. Units per box: 1.		
	Model: 12SB44P Voltage: 12V Capacity: 44Ah (C20) Int. resistance: 6 mOhm	Max charge I: 9 Amps Max discharge I: 500 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 196mm. Width: 164mm. Height: 171mm (171mm). Weight: 14kg. Units per box: 1.		
	Model: 12SB70P Voltage: 12V Capacity: 70Ah (C20) Int. resistance: 5.5 mOhm	Max charge I: 14 Amps Max discharge I: 800 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: Version 1. Length: 350mm. Width: 166mm. Height: 174mm (174mm). Weight: 25kg. 1 per box Version 2. Length: 257mm. Width: 166mm. Height: 214mm (214mm). Weight: 25kg. 1 per box		
	Model: 12SB100P Voltage: 12V Capacity: 100Ah (C20) Int. resistance: 3.9 mOhm	Max charge I: 20 Amps Max discharge I: 900 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 304mm. Width: 166mm. Height: 214mm (214mm). Weight: 30kg. Units per box: 1.		
	Model: 12SB120P Voltage: 12V Capacity: 120Ah (C20) Int. resistance: 3.1 mOhm	Max charge I: 24 Amps Max discharge I: 1100 Amps (5 sec) Cyclic charge Volts: 14.7 to 15V Standby charge Volts: 13.5 to 13.8V
Length: 406mm. Width: 172mm. Height: 234mm (234mm). Weight: 39kg. Units per box: 1.		
	Model: BR100 (6TL) Voltage: 12V Capacity: 100Ah (C5 to 9V 27°C)	DIN standard VG 96924-2 NSN: 6140-12-190-9027
Length: 284mm. Width: 267mm. Height: 230mm. Weight: 39.5kg. Military vehicle applications (leopard tank and others)		